



**Technical Parameters:**

Working platform length-----	5500mm(18' / 216.54")
Working platform width-----	2100mm(7' / 82.68")
Working platform height-----	560mm(2' / 22.05")
Working platform thickness-----	140mm(0.5' / 5.51")
Hydraulic system max working pressure-----	70MPa
Tower column oil cylinder pulling capacity-----	10MT(9.8KN)
Tower column pulling range-----	360°
Drive air source pressure -----	0.7MPa
Max lifting weight-----	3000KG(6613 Ibs)
Equipment gross weight-----	2500KG(5511 Ibs)

**DL-1900 enjoys the following features:**

- 1, Tilt-bed design allows easy loading and unloading with its loading ramps.
- 2, Excellent movable ten-ton tower 360 pulling operation, freely and flexibly. The hydraulic cylinder works vertically without any components force consumption, powerful and accurate tensile force.
- 3, Advanced universal clamping system is available for various vehicles, with these high-precision clamps, you can quickly anchor any vehicles rock-solid accurately, in any height and angles needed.
- 4, The mechanical measurement system is more suitable for plate technicians.
- 5, Hydraulic system imported from ENERPAC USA, powerful and reliable. With high-strength clamp chains and entire series of pulling accessories, you can almost recover any car distortion with ease.
- 6, Provide all series of auto database from Milchell USA and some other auto companies.
- 7, Many humanity engineering design for user to operate easily and comfortably.
- 8, Elegant technique is incomparable.